

DPQ-82 AL



Specification

| Thermal efficiency | |
|---|--|
| U _w *: Coefficient value for reference design | 0,77 W/m ² K |
| U factor*: | 0,14* Btu/h·ft ² ·F |
| *: | Glass 4/18/4/18/4. gas: argon, warm edge spacer, window size 48 7/16in x 58 4/16in (1230mm x 1480mm) |
| Profile | |
| Profile name: | DPQ-82 AL |
| Installation depth: | 87 mm |
| Number of chambers: | 7 |
| Thermal break: | --- |
| Number of seals: | 3 |
| Glass | |
| Glazing package: | 4/18/4/18/4 |
| U _g value: | 0,5 W/m ² K |
| Glazing Package Thickness: | 48 mm |
| Sound insulation of available glazing: | --- |
| Fittings | |

| | |
|---|-----------------------------------|
| Type: | --- |
| Hinges: | surface |
| Anti-theft protection: | 2 Anti-theft catches |
| Microventilation: | yes |
| Other: | --- |
| Handle | |
| Colors: | --- |
| Handle model: | 1006 |
| Dimensions | |
| Maximum window width - single sash: | 1500 mm |
| Maximum window height - single sash: | 2575 mm |
| Maximum window width - double sash with a movable post: | 2085 mm |
| Maximum window height - double sash with a movable post: | 2480 mm |
| Maximum sash area: | 2,25 m ² |
| Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg): | 3500 x 2900 mm lub 2900 x 3500 mm |

Photos

